

## DECLARATION OF PERFORMANCE

(according to regulation EU No 305/2011)

No. Strip S355J2

**Strip S355J2 / 1.0577 according EN 10025-2**

To be used in-welded, bolted and riveted structures

**Head Office: ParkerSteel Limited**  
**Vauxhall Road, Canterbury**  
**Kent CT1 1HD**

Tel: 01227 783333

Website: www.parkersteel.co.uk

View DOP: www.parkersteel.co.uk/dop

**UKCA Marking Notified Body (No. 2273)**

Steel Construction Certification Scheme

4 Whitehall Court, Westminster


London, SW1A 2ES

Tel: 020 7839 8566

Website: www.steelconstruction.org

System of assesment and verification of constancy of  
 performance of the product:  
 System 2+

Steel Construction Certificate Scheme has performed (i) intial  
 inspection of the manufacturing plant and factory product  
 control and (ii) continuous surveillance, assessment and  
 evaluation of factory production control and issued Factory  
 Production Control certificate 2273-CPR-0025 and Welding  
 Certificate 2273-CPR-0025-WC.



**Dylan Alexander**  
 Managing Director  
 ParkerSteel Limited

Date:  
 December 2022

Essential Characteristic	Performance		Harmonised Technical Specification	
Tolerance on dimensions and shape	Dimensions		EN 10051	
Yield strength (transverse)	Nominal thickness (mm)		Values Min (MPa)	
	>	<		
	-	16	355	
Tensile strength (transverse)	Nominal thickness (mm)		Values Min (MPa)	
	>	<=	min	max
	-	16	510	680
	3	16	470	630
Elongation (transverse)	Nominal thickness (mm)		Values Min (% , 80mm)	
	>	<=		
		1	14	
	1	1.5	15	
	1.5	2	16	
	2	2.5	17	
	2.5	3	18	
	Nominal thickness (mm)		Values Min (% , 5.65√so)	
3	16	22		
Impact strength (longitudinal)	J2		27J @ 20°C	
Weldability CEV	Nominal thickness (mm)		Values Max (%)	
	>	<=		
	-	16	0.45	
Durability	Nominal thickness (mm)		Values Max (%)	
	-	<=16	C:	0,20
			Si:	0,55
			Mn:	1,60
			P:	0,025
			S:	0,025
			Cu:	0,55

EN10025-1 2004

# UK CA

2273

Head Office: ParkerSteel Limited  
 Vauxhall Road  
 Canterbury  
 Kent  
 CT1 1HD

Strip S355J2

EN 10025-1 - 2004  
 Strip S355J2 / 1.0577

To be used in-welded, bolted and riveted structures  
 Tolerances on dimensions : Strip EN10051

Elongation:  
 Tensile Strength:  
 Yield Strength: EN10025-2  
 Impact Strength:  
 Weldability:  
 Durability:  
 Dangerous Substances: No Performance Determined