

DECLARATION OF PERFORMANCE

(according to regulation EU No 305/2011)

No. Plate S275JR

Plate S275JR / 1.0044 according EN 10025-2

To be used in-welded, bolted and riveted structures

Head Office: ParkerSteel Limited

Vauxhall Road, Canterbury

Kent CT1 1HD

Tel: 01227 783333

Website: www.parkersteel.co.uk

View DOP: www.parkersteel.co.uk/dop

UKCA Marking Notified Body (No. 2273)

Steel Construction Certification Scheme

4 Whitehall Court, Westminster


London, SW1A 2ES

Tel: 020 7839 8566

Website: www.steelconstruction.org

System of assesment and verification of constancy of performance of the product:
System 2+

Steel Construction Certificate Scheme has performed (i) initial inspection of the manufacturing plant and factory product control and (ii) continuous surveillance, assessment and evaluation of factory production control and issued Factory Production Control certificate 2273-CPR-0025 and Welding Certificate 2273-CPR-0025-WC.



Essential Characteristic	Performance		Harmonised Technical Specification	
Tolerance on dimensions and shape	Thickness		EN 10029	
	Flatness		EN 10029	
Yield strength (transverse)	Nominal thickness (mm)		Values Min (MPa)	
	>	<=		
	-	16	275	
	16	40	265	
	40	63	255	
	63	80	245	
	80	100	235	
Tensile strength (transverse)	Nominal thickness (mm)		Values Min (MPa)	
	>	<=	min	max
	5	100	410	560
	100	150	400	540
	Elongation (transverse)		Values Min (% , 5.65√s ₀)	
>	<=			
5	40	21		
40	63	20		
63	100	19		
100	150	19		
Impact strength (longitudinal)	JR		27J @ + 20°C	
	J0		27J @ - 0°C	
	J2		27J @ 20°C	
Weldability CEV	Nominal thickness (mm)		Values Max (%)	
	>	<=		
	-	40	0.40	
	40	150	0.42	
Durability	Nominal thickness (mm)		Values Max (%)	
	-	<=40	C: 0,21	
			Mn: 1,50	
			P: 0,035	
			S: 0,035	
			N: 0,012	
			Cu: 0,55	
			C: 0,22	
	>40	150	C: 0,22	
			Mn: 1,50	
			P: 0,035	
			S: 0,035	
			N: 0,012	
Cu: 0,55				

EN10025-1 2004

UK CA

2273

Head Office: ParkerSteel Limited
Vauxhall Road
Canterbury
Kent
CT1 1HD

Plate S275JR

EN 10025-1 - 2004
Plate S275JR / 1.0044

To be used in-welded, bolted and riveted structures
Tolerances on dimensions : Plate EN10029

Elongation:
Tensile Strength:
Yield Strength: EN10025-2
Impact Strength:
Weldability:
Durability:
Dangerous Substances: No Performance Determined